

RECEIVED
CENTRAL FAX CENTER

MAY 0 5 2006

Chris Keirs 832-446-2406 Ckeirs@counselip.com

FAX TRANSMISSION COVER SHEET

Date: 5/5/2006 8:42 AM

To: USPTO

Fax: 571 273-8300

From: Chris Keirs

Client/Matter #: 221-0073US

Re: s/n 10/679,908

Pages (including cover page): 5

COMMENTS:

Attached for filing in connection with application serial no. 10/679,908 filed 10/06/2003 and entitled Undersea Hydraulic Coupling for Use With Manifold Plates is:

4-page Reply Brief

CONFIDENTIALITY NOTICE

This communication is only for the person named above. Unless otherwise indicated, it contains information that is confidential, privileged or exempt from disclosure under applicable law. If you are not the person named above, or responsible for delivering it to that person, be aware that disclosure, copying, distribution or use of this communication is strictly prohibited. If you have received it in error, or are uncertain as to its proper handling, please immediately notify us by collect telephone and mail the original to us at the above address. Thank you.

MAY 0 5 2006

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:

§ Confirmation No. 3821

Robert E. Smith III

§ Confirmation No. 3821

Serial Number: 10/679,908

§ Examiner: Thomas A. Beach

Filed: 10/06/2003

§ Group art unit: 3671

For: UNDERSEA HYDRAULIC

COUPLING FOR USE WITH

MANIFOLD PLATES

§ Atty Docket No. 221-0073US

Commissioner for Patents P. O. Box 1450 Alexandria, Virginia 22313-1450

REPLY BRIEF

The Examiner's Answer states that the following grounds of rejection are applicable to the appealed claims. Applicant's reply to each is set forth in square brackets.

"Claims 1-9 are rejected under 35 U.S.C. 102(b) as being anticipated by Smith 5,015,016. Smith shows an undersea hydraulic coupling member having a tail 74 (see figure 3), at least one substantially rigid positioning member 26 associated with the tail, wherein the substantially rigid positioning members are in contact with the inner bore 73 of a manifold plate when the tail is inserted through the manifold plate (unnumbered in figure 1).

[Even ignoring the issue of whether male probe 74 of the Smith016 connector may be considered a "tail" as that term is used in the subject

CERTIFICATE OF TRANSMISSION	
I hereby certify that this document together with an "attached" is being sent by facsimile machine to tel	y papers referred to herein as "enclosed" or enhance number, 571, 273-8300 on the date
written below.	ephone number of 1 270 cood on the cane
By: Christopher D. Keirs, Reg. No. 32,248	Date: MAY 5, 2006
Christopher D. Keirs, Reg. No. 32,248	Date. 1

s/n 10/679,908 221-0073US

claims, element 26 of the Smith016 reference is simply not in contact with the inner bore of a manifold plate as required by claim 1. Rather, element 26 is provided "for sealing between the receiving bore 61 and the outer circumference of the male member 13." {col. 6; lines 9-14} The manifold plates are shown in phantom at the top and bottom of Fig. 6 of the Smith016 reference. As may be seen in Fig. 6, element 26 is not in contact with element 73 as the Examiner's Answer contends.]

"As concerns claims 2 & 8, Smith shows the substantially rigid positioning member is an o-ring 26 (figure 3).

[Element 26 of Smith016 is described as an "annular or axial soft seal." However, the seals in hydraulic couplings that engage the male member about its circumference "generally resemble O-rings." {col. 1; lines 26-32}]

"As concerns claims 3 & 9, Smith shows the substantially rigid positioning member is elastomeric."

[The annular soft seals 26 and 27 are of a relatively pliable material, for example, rubber or synthetic elastomer. {col. 6; lines 14-16}]

"As concerns claim 4, Smith shows a retaining ring to attach the hydraulic coupling member to the manifold plate (figures 1 and 3)."

[The coupling members of Smith016 are attached to the manifold plates by threads on their tails. "Threads 73 may be added to the external surface to facilitate attachment to a coupling manifold, as explained above, or the external surface may be machined smooth and the probe 13 may be attached to the manifold by means of set screws (not shown)." {col. 7; lines 8-12} The disadvantages of this attachment method are what the subject invention addresses.]

s/n 10/679,908 221-0073US

"As concerns claim 5, Smith shows the retaining ring is held in place with a snap ring 55 contained in a groove in the tail (figure 3)."

[Element 55 of Smith016 is not a snap ring. It is an annular metal C-seal. {col. 5; line 37} The only element of Smith016 resembling a snap ring is retainer clip 24 which secures sleeve member 22 in the bore of the female member. "The movement of the sleeve member 22 is limited by retainer clip 24, in the female member bore." {col. 8; lines 46-48}]

"As concerns claim 6, Smith shows the tail has at least two grooves for containing the snap ring to accommodate manifold plates of different thicknesses (figure 3)."

[The Examiner contends that element 74 of Smith016 may be considered a "tail." As may be clearly seen in the cross-sectional view of Figure 4, probe 74 of the Smith016 connector has no grooves for containing a snap ring.]

Summary

The claims require a hydraulic coupling comprising a tail with an associated, substantially rigid, positioning member that is in contact with the inner bore of a manifold plate when the tail is inserted through the manifold plate. The tails of the male and female members of the Smith016 connector are threaded for conventional mounting on manifold plates. Moreover the cited reference has no substantially rigid, positioning member that is in contact with the inner bore of a manifold plate when the tail is inserted through the manifold plate. Accordingly, the cited reference does not anticipate the claimed invention under §102(b).

s/n 10/679,908 221-0073US

Respectfully submitted:

Christopher D. Keirs

Reg. No. 32,248

Attorney for Applicant(s)

Wong Cabello Lutsch Rutherford & Brucculeri LLP

20333 State Hwy. 249 Suite 600

Houston, TX 77070

832 446-2406

Fax: 832 446-2424 ckeirs@counselip.com